



MODEL NUMBER	CONNECTION SIZE	
	TEST SIDE	PROCESS SIDE
VTPT - 02	3/8" UNF	1/4" *
VTPT - 512	3/8" UNF	1/2" *
PLEASE SPECIFY PROCESS CONNECTION THREADING STANDARD (NPT / BSP), AND APPLICATION		

- * INSTANT ACCESS TO TEST TEMPERATURE AND / OR PRESSURE.
- * INJECT OR TAKE SAMPLES OF GAS OR LIQUID FROM PIPE OR VESSEL WHILE UNDER PRESSURE.
- * REDUCE NEED FOR COSTLY, PERMANENTLY INSTALLED GAUGES.
- * CONDUCT TESTS AT SPECIFIC KEY LOCATIONS.
- * **BODY CONSTRUCTION** : BRASS
- * **CORE CONSTRUCTION** : NEOPRENE (FOR WATER AND AIR)
EPDM (FOR STEAM AND HIGH TEMPERATURE FLUID)
NITRILE RUBBER (FOR OIL)
- * **MAXIMUM OPERATING PRESSURE** : 500 PSI (WATER)
250 PSI (STEAM)
- * **TEMPERATURE RANGE** : -30°F TO 250°F
- * **APPLICATION** : WATER, AIR, OIL AND STEAM
- * **INSTALLATION** : USE FACTORY SUPPLIED WELDABLE STEEL SOCKET
(ACCESSORY) FOR INSTALLATION OF TEST PLUGS.

Notes / Remarks :

VIBRATION MANAGEMENT CORPORATION

5930 THOMAS ROAD,
HOUSTON - TEXAS 77041 , USA

Internet address:
www.vimco.biz

Project :
Client :
Consultant :
Representative:

Title : **PRESSURE / TEMPERATURE
TEST PLUG**

Drawing no.
S-2700.16

Rev. 1