

IVS - 150

DESCRIPTION:

IVS-150 is a water based acrylic sealant. It is fire resistant and used in all heating, ventilation, and air conditioning ductwork systems.

USES:

IVS-150 can be applied by trowel, brush, or extrusion. It readily fills the joints of round and rectangular ductwork, grilles and mixing boxes.

ADVANTAGES:

IVS-150 duct sealant is safe to use because it is water based and thixotropic in nature. It adheres firmly to the joints in the duct system to form a strong and resilient seal. It is resistant to fire, oxidation, moisture, water and

APPLICATION:

All duct work surfaces must be clean, dry and free of oil and dirt prior to application. Do not dilute this product prior to application. When finished applying duct sealant, clean all tools and metal surfaces with hot water while the sealant is still wet. Allow 2 to 3 days drying time before applying air pressure to the duct work.

SPECIFICATIONS:

IVS-150 meets the requirements of NFPA standard 90-A. It also meets dry film hazard requirements of GSA.

COLOR	LIGHT GRAY (12), LIGHT RED (20)	
WET WEIGHT	10.0 LBS / US GALLON	
AVERAGE NON-VOLATILE	71% BY WEIGHT	
TEMP. RANGE	-20°F to 200°F	
DRYING TIME	2 - 3 DAYS	
COVERAGE (varies with thickness)	30 - 120 FT. / 10TH GALLON CARTRIDGE	
SURFACE BURNING CHARACTERISTICS (ASTME-84)	SURFACE	: 1/4" ASBESTOS CEMENT BOARD
	FLAME SPREAD INDEX	: 5
	SMOKE DEVELOPED INDEX	: 0

ALSO AVAILABLE IVS-220 (NEW PRODUCT) SILICON DUCT SEALANT, FOR SIMILAR USE, APPLICATION AND SPECIFICATIONS AS THAT OF ACRYLIC SEALANT.